



RECOMMENDED PANEL CUTOUT
SCALE 2:1

- △ CAVITY IDENTIFICATION CHARACTERS ON FRONT AND REAR FACE.
- △ RECEPTACLE: NYLON, UL 94V-0 RATED, BLACK.
CONTACT AND POST: BRASS.
SPRING: STAINLESS STEEL.
- △ SOCKET CONTACT AND POST: 2.54um [.000100] MIN TIN-LEAD OVER 1.27um [.000050] MIN NICKEL.
- △ SOCKET CONTACT AND POST: 2.54um [.000100] MIN TIN OVER 1.27um [.000050] MIN NICKEL.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OBSOLETE	△	B, C, D, E, F, H, I, J, L, M, N	1-213928-4
	△	A, B, C, D, E, F, G, H, K	1-213928-3
	△	A, B, C, D, E, K	1-213928-2
	△	ALL	1-213928-1
OBSOLETE	△	B, C, D, E, F, H, I, J, L, M, N	213928-4
	△	A, B, C, D, E, F, G, H, K	213928-3
	△	A, B, C, D, E, K	213928-2
	△	ALL	213928-1
FINISH		POSITIONS LOADED	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN C. OBERMAN 31 OCT 95	STE TE Connectivity
0 PLC ± -	1 PLC ± -	1 NOV 95	
2 PLC ± 0.13 [.005]	3 PLC ± -	2 NOV 95	
4 PLC ± -	ANGLES ± -		

APVD: R. BYERS
NAME: R. STONE
PRODUCT SPEC: -
APPLICATION SPEC: -
MATERIAL: -
FINISH: -
WEIGHT: -
CUSTOMER DRAWING

SIZE: A1
CAGE CODE: 00779
DRAWING NO: 213928
SCALE: 4:1
SHEET: 1 of 1
REV: C2