



1	GRAY (DRAIN)
2	RED +V
3	BLACK -V
4	WHITE CAN H
5	BLUE CAN L

WIRING DIAGRAM

6	1	LABEL	MYLAR	BLACK/YELLOW
5	1	O-RING	NITRILE	BLACK
4	1	LOCKNUT	STAINLESS STEEL	PASSIVATED
3	3	INSULATOR, 5/C, DC KEY	NYLON	BLACK
2	5	CONTACTS	Cu ALLOY	GOLD PLATED
1	1	RECEPTACLE SHELL	STAINLESS STEEL	PASSIVATED
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

95 WAS 91, ADD REF.  
 EC NO: ETC2008-0096  
 DRWR:RSTONE 2007/11/15  
 CHKD:J.MACNEIL 2007/12/05  
 APPR:JMACNEIL 2007/12/05

QUALITY SYMBOLS  
  
 DESCRIPTION  
 REV

GENERAL TOLERANCES (UNLESS SPECIFIED)	
	mm INCH
4 PLACES	± .005 ± .0005
3 PLACES	± .005 ± .0005
2 PLACES	± .005 ± .0005
1 PLACE	± .005 ± .0005
ANGULAR ±1/2°	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE IN/MM	
DRAWN BY	DATE
R.STONE	2007/10/05
CHECKED BY	DATE
J.MACNEIL	2007/10/10
APPROVED BY	DATE
J.MACNEIL	2007/10/10
MATERIAL NO. 848649004	

SCALE 2:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
TITLE MICRO-C RECEPTACLE FEMALE, SS, DEVICE NET		
MOLEX INCORPORATED		
MATERIAL NO. 848649004	DOCUMENT NO. SD-84864-004	SHEET NO. 1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		