



## Power MOSFET

### PRODUCT SUMMARY

|                           |                        |       |
|---------------------------|------------------------|-------|
| $V_{DS}$ (V)              | 500                    |       |
| $R_{DS(on)}$ ( $\Omega$ ) | $V_{GS} = 10\text{ V}$ | 0.450 |
| $Q_g$ (Max.) (nC)         | 81                     |       |
| $Q_{gs}$ (nC)             | 20                     |       |
| $Q_{gd}$ (nC)             | 36                     |       |
| Configuration             | Single                 |       |

TO-220AB



N-Channel MOSFET

### FEATURES

- Lower Gate Charge  $Q_g$  Results in Simpler Drive Requirements
- Improved Gate, Avalanche and Dynamic  $dV/dt$  Ruggedness
- Fully Characterized Capacitance and Avalanche Voltage
- Compliant to RoHS Directive 2002/95/EC



RoHS\*  
Available

### APPLICATIONS

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supplies
- High Speed Power Switching

### ORDERING INFORMATION

|                |                                 |
|----------------|---------------------------------|
| Package        | TO-220AB                        |
| Lead (Pb)-free | IRFB13N50APbF<br>SiHFB13N50A-E3 |
| SnPb           | IRFB13N50A<br>SiHFB13N50A       |

### ABSOLUTE MAXIMUM RATINGS ( $T_C = 25\text{ }^\circ\text{C}$ , unless otherwise noted)

| PARAMETER                                        |                         |                         | SYMBOL                            | LIMIT            | UNIT  |
|--------------------------------------------------|-------------------------|-------------------------|-----------------------------------|------------------|-------|
| Drain-Source Voltage                             |                         |                         | V <sub>DS</sub>                   | 500              | V     |
| Gate-Source Voltage                              |                         |                         | V <sub>GS</sub>                   | ± 30             |       |
| Continuous Drain Current                         | V <sub>GS</sub> at 10 V | T <sub>C</sub> = 25 °C  | I <sub>D</sub>                    | 14               | A     |
|                                                  |                         | T <sub>C</sub> = 100 °C |                                   | 9.1              |       |
| Pulsed Drain Current <sup>a</sup>                |                         |                         | I <sub>DM</sub>                   | 56               |       |
| Linear Derating Factor                           |                         |                         |                                   | 2.0              | W/°C  |
| Single Pulse Avalanche Energy <sup>b</sup>       |                         |                         | E <sub>AS</sub>                   | 560              | mJ    |
| Avalanche Current <sup>a</sup>                   |                         |                         | I <sub>AR</sub>                   | 14               | A     |
| Repetitive Avalanche Energy <sup>a</sup>         |                         |                         | E <sub>AR</sub>                   | 25               | mJ    |
| Maximum Power Dissipation                        | T <sub>C</sub> = 25 °C  |                         | P <sub>D</sub>                    | 250              | W     |
| Peak Diode Recovery dV/dt <sup>c</sup>           |                         |                         | dV/dt                             | 9.2              | V/ns  |
| Operating Junction and Storage Temperature Range |                         |                         | T <sub>J</sub> , T <sub>stg</sub> | - 55 to + 150    | °C    |
| Soldering Recommendations (Peak Temperature)     | for 10 s                |                         |                                   | 300 <sup>d</sup> |       |
| Mounting Torque                                  | 6-32 or M3 screw        |                         |                                   | 10               |       |
|                                                  |                         |                         |                                   | 1.1              | N · m |

#### Notes

- Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).
- Starting  $T_J = 25\text{ }^\circ\text{C}$ ,  $L = 5.7\text{ mH}$ ,  $R_g = 25\text{ }\Omega$ ,  $I_{AS} = 14\text{ A}$ ,  $dV/dt = 7.6\text{ V/ns}$  (see fig. 12a).
- $I_{SD} \leq 14\text{ A}$ ,  $dI/dt \leq 250\text{ A}/\mu\text{s}$ ,  $V_{DD} \leq V_{DS}$ ,  $T_J \leq 150\text{ }^\circ\text{C}$ .
- 1.6 mm from case.

\* Pb containing terminations are not RoHS compliant, exemptions may apply

**THERMAL RESISTANCE RATINGS**

| PARAMETER                          | SYMBOL     | TYP. | MAX. | UNIT |
|------------------------------------|------------|------|------|------|
| Maximum Junction-to-Ambient        | $R_{thJA}$ | -    | 62   | °C/W |
| Case-to-Sink, Flat, Greasd Surface | $R_{thCS}$ | 0.50 | -    |      |
| Maximum Junction-to-Case (Drain)   | $R_{thJC}$ | -    | 0.50 |      |


**SPECIFICATIONS** ( $T_J = 25\text{ }^{\circ}\text{C}$ , unless otherwise noted)

| PARAMETER                                 | SYMBOL                           | TEST CONDITIONS                                                                                                                                         |                                                                                                        | MIN. | TYP. | MAX.  | UNIT |
|-------------------------------------------|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|------|------|-------|------|
| Static                                    |                                  |                                                                                                                                                         |                                                                                                        |      |      |       |      |
| Drain-Source Breakdown Voltage            | V <sub>DS</sub>                  | V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA                                                                                                          |                                                                                                        | 500  | -    | -     | V    |
| V <sub>DS</sub> Temperature Coefficient   | ΔV <sub>DS</sub> /T <sub>J</sub> | Reference to 25 °C, I <sub>D</sub> = 1 mA                                                                                                               |                                                                                                        | -    | 0.55 | -     | V/°C |
| Gate-Source Threshold Voltage             | V <sub>GS(th)</sub>              | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA                                                                                             |                                                                                                        | 2.0  | -    | 4.0   | V    |
| Gate-Source Leakage                       | I <sub>GSS</sub>                 | V <sub>GS</sub> = ± 30 V                                                                                                                                |                                                                                                        | -    | -    | ± 100 | nA   |
| Zero Gate Voltage Drain Current           | I <sub>DSS</sub>                 | V <sub>DS</sub> = 500 V, V <sub>GS</sub> = 0 V                                                                                                          |                                                                                                        | -    | -    | 25    | μA   |
|                                           |                                  | V <sub>DS</sub> = 400 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 125 °C                                                                                 |                                                                                                        | -    | -    | 250   |      |
| Drain-Source On-State Resistance          | R <sub>DS(on)</sub>              | V <sub>GS</sub> = 10 V                                                                                                                                  | I <sub>D</sub> = 8.4 A <sup>b</sup>                                                                    | -    | -    | 0.450 | Ω    |
| Forward Transconductance                  | g <sub>fs</sub>                  | V <sub>DS</sub> = 50 V, I <sub>D</sub> = 8.4 A                                                                                                          |                                                                                                        | 8.1  | -    | -     | S    |
| Dynamic                                   |                                  |                                                                                                                                                         |                                                                                                        |      |      |       |      |
| Input Capacitance                         | C <sub>ISS</sub>                 | V <sub>GS</sub> = 0 V,<br>V <sub>DS</sub> = 25 V,<br>f = 1.0 MHz, see fig. 5                                                                            |                                                                                                        | -    | 1910 | -     | pF   |
| Output Capacitance                        | C <sub>OSS</sub>                 |                                                                                                                                                         |                                                                                                        | -    | 290  | -     |      |
| Reverse Transfer Capacitance              | C <sub>RSS</sub>                 |                                                                                                                                                         |                                                                                                        | -    | 11   | -     |      |
| Output Capacitance                        | C <sub>OSS</sub>                 | V <sub>GS</sub> = 0 V                                                                                                                                   | V <sub>DS</sub> = 1.0 V, f = 1.0 MHz                                                                   | -    | 2730 | -     |      |
|                                           |                                  |                                                                                                                                                         | V <sub>DS</sub> = 400 V, f = 1.0 MHz                                                                   | -    | 82   | -     |      |
| Effective Output Capacitance              | C <sub>OSS eff.</sub>            |                                                                                                                                                         | V <sub>DS</sub> = 0 V to 400 V <sup>c</sup>                                                            | -    | 160  | -     |      |
| Total Gate Charge                         | Q <sub>g</sub>                   | V <sub>GS</sub> = 10 V                                                                                                                                  | I <sub>D</sub> = 14 A, V <sub>DS</sub> = 400 V,<br>see fig. 6 and 13 <sup>b</sup>                      | -    | -    | 81    | nC   |
| Gate-Source Charge                        | Q <sub>gs</sub>                  |                                                                                                                                                         |                                                                                                        | -    | -    | 20    |      |
| Gate-Drain Charge                         | Q <sub>gd</sub>                  |                                                                                                                                                         |                                                                                                        | -    | -    | 36    |      |
| Turn-On Delay Time                        | t <sub>d(on)</sub>               | V <sub>GS</sub> = 10 V                                                                                                                                  | V <sub>DD</sub> = 250 V, I <sub>D</sub> = 14 A,<br>R <sub>g</sub> = 7.5 Ω,<br>see fig. 10 <sup>b</sup> | -    | 15   | -     | ns   |
| Rise Time                                 | t <sub>r</sub>                   |                                                                                                                                                         |                                                                                                        | -    | 39   | -     |      |
| Turn-Off Delay Time                       | t <sub>d(off)</sub>              |                                                                                                                                                         |                                                                                                        | -    | 39   | -     |      |
| Fall Time                                 | t <sub>f</sub>                   |                                                                                                                                                         |                                                                                                        | -    | 31   | -     |      |
| Drain-Source Body Diode Characteristics   |                                  |                                                                                                                                                         |                                                                                                        |      |      |       |      |
| Continuous Source-Drain Diode Current     | I <sub>S</sub>                   | MOSFET symbol showing the integral reverse p - n junction diode<br> |                                                                                                        | -    | -    | 14    | A    |
| Pulsed Diode Forward Current <sup>a</sup> | I <sub>SM</sub>                  |                                                                                                                                                         |                                                                                                        | -    | -    | 56    |      |
| Body Diode Voltage                        | V <sub>SD</sub>                  | T <sub>J</sub> = 25 °C, I <sub>S</sub> = 14 A, V <sub>GS</sub> = 0 V <sup>b</sup>                                                                       |                                                                                                        | -    | -    | 1.5   | V    |
| Body Diode Reverse Recovery Time          | t <sub>rr</sub>                  | T <sub>J</sub> = 25 °C, I <sub>F</sub> = 14 A,<br>T <sub>J</sub> = 125 °C, di/dt = 100 A/μs <sup>b</sup>                                                |                                                                                                        | -    | 370  | 550   | ns   |
| Body Diode Reverse Recovery Charge        | Q <sub>rr</sub>                  |                                                                                                                                                         |                                                                                                        | -    | 4.4  | 6.5   | μC   |
| Body Diode Reverse Recovery Current       | I <sub>RRM</sub>                 |                                                                                                                                                         |                                                                                                        | -    | 21   | 31    | A    |
| Forward Turn-On Time                      | t <sub>on</sub>                  | Intrinsic turn-on time is negligible (turn-on is dominated by L <sub>S</sub> and L <sub>D</sub> )                                                       |                                                                                                        |      |      |       |      |


**Notes**

- a. Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).  
b. Pulse width  $\leq 300\text{ }\mu\text{s}$ ; duty cycle  $\leq 2\%$ .  
c.  $C_{oss\text{ eff.}}$  is a fixed capacitance that gives the same charging time as  $C_{oss}$  while  $V_{DS}$  is rising from 0 % to 80 %  $V_{DS}$ .


## TYPICAL CHARACTERISTICS (25 °C, unless otherwise noted)




**Fig. 1 - Typical Output Characteristics**



**Fig. 3 - Typical Transfer Characteristics**



**Fig. 2 - Typical Output Characteristics**



**Fig. 4 - Normalized On-Resistance vs. Temperature**




Fig. 5 - Typical Capacitance vs. Drain-to-Source Voltage




Fig. 7 - Typical Source-Drain Diode Forward Voltage




Fig. 6 - Typical Gate Charge vs. Gate-to-Source Voltage




Fig. 8 - Maximum Safe Operating Area




Fig. 9 - Maximum Drain Current vs. Case Temperature




Fig. 10a - Switching Time Test Circuit




Fig. 10b - Switching Time Waveforms




Fig. 11 - Maximum Effective Transient Thermal Impedance, Junction-to-Case




Fig. 12a - Unclamped Inductive Test Circuit




Fig. 12b - Unclamped Inductive Waveforms




Fig. 12c - Maximum Avalanche Energy vs. Drain Current




Fig. 13a - Basic Gate Charge Waveform




Fig. 13b - Gate Charge Test Circuit




# IRFB13N50A, SiHFB13N50A

Vishay Siliconix



reliability data, see [www.vishay.com/ppg?91095](http://www.vishay.com/ppg?91095).

## TO-220-1




| DIM.            | MILLIMETERS |       | INCHES |       |
|-----------------|-------------|-------|--------|-------|
|                 | MIN.        | MAX.  | MIN.   | MAX.  |
| A               | 4.24        | 4.65  | 0.167  | 0.183 |
| b               | 0.69        | 1.02  | 0.027  | 0.040 |
| b(1)            | 1.14        | 1.78  | 0.045  | 0.070 |
| c               | 0.36        | 0.61  | 0.014  | 0.024 |
| D               | 14.33       | 15.85 | 0.564  | 0.624 |
| E               | 9.96        | 10.52 | 0.392  | 0.414 |
| e               | 2.41        | 2.67  | 0.095  | 0.105 |
| e(1)            | 4.88        | 5.28  | 0.192  | 0.208 |
| F               | 1.14        | 1.40  | 0.045  | 0.055 |
| H(1)            | 6.10        | 6.71  | 0.240  | 0.264 |
| J(1)            | 2.41        | 2.92  | 0.095  | 0.115 |
| L               | 13.36       | 14.40 | 0.526  | 0.567 |
| L(1)            | 3.33        | 4.04  | 0.131  | 0.159 |
| $\varnothing P$ | 3.53        | 3.94  | 0.139  | 0.155 |
| Q               | 2.54        | 3.00  | 0.100  | 0.118 |

ECN: X15-0364-Rev. C, 14-Dec-15  
DWG: 6031

### Note

- M\* = 0.052 inches to 0.064 inches (dimension including protrusion), heatsink hole for HVM





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**